

# ViewSonic®

## PJ750 Projector

### Ultra-Portable Series



- **High-brightness 2,200 lumen portable projector**
- **Native 1024x768 XGA resolution**
- **Easy setup and auto tuning**  
One-touch setup button for fast, easy sync and sharp focus.
- **Whisper-mode operations**  
Whisper-mode for extended lamp life and low noise output.
- **Component video for enhanced video quality**  
View HDTV signals and other video signals at maximum performance levels.
- **Ultimate flexibility with multiple computer inputs**  
Connect two computers simultaneously for dynamic meetings.
- **User-replaceable extended-life lamp**  
Extended lamp life up to 4,000 hours.\*
- **Three-year limited warranty**  
Covered by a three-year limited warranty and one-year Express Exchange® program.\*\*
- **Industry-leading one-year lamp warranty**  
Extended-life lamp, warranted for a full year.\*\*

### PJ750 high-brightness, ultra-portable XGA projector.

The ViewSonic PJ750 delivers exceptionally bright presentations. With 2,200 lumens, 1024x768 XGA resolution and high contrast, this projector delivers clear, crisp images, even in well-lit rooms. Easy to use, the full-featured PJ750 offers zoom and digital keystone correction as well as multiple computer and video inputs and outputs for greater flexibility. Whisper-mode will make the most out of your investment by extending the lamp life and reducing noise output to whisper-quiet levels. Using the PJ750 you can be confident of presenting a positive image anytime, anywhere.



**ViewSonic®**  
*See the difference.®*

# ViewSonic®

## PJ750 Projector



- **Digital keystone correction**

Squares up the picture when projecting at an angle.

- **RGB-out capability**

Allows you to view your presentation on a monitor, too.

- **Free 24/7 customer support†**

- **Accessories expand your options**

Hard carrying case w/cart function (PRJ-HCA-001)  
 Spare lamp (RLC-160-03A)  
 Ceiling/wall mount kit (PM-750)  
 Express Exchange® service (EE-LB-02)



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

### PORTABLE HIGH-BRIGHTNESS PROJECTOR

|                        |   |   |
|------------------------|---|---|
| LCD                    | <b>Type</b><br><b>Pixel Format</b><br><b>Lens</b>   | 0.9" Polysilicon (x3) stripe pixel TFT active matrix<br>1024 horizontal x 768 vertical<br>Manual zoom/focus (1:1.3x)  |
| DISPLAY                | <b>Size</b><br><b>Throw Distance</b><br><b>Lamp</b><br><b>Brightness</b><br><b>Contrast Ratio</b>   | 30"–300" (measured diagonally)<br>1.2m–5.7m (3.9'–51.0')<br>200W UHB compact, 4,000 hour rating*<br>2,200 lumens<br>400:1   |
| AUDIO                  | <b>Speakers</b><br><b>Power</b>   | Stereo<br>1Wx2  |
| INPUT SIGNAL           | <b>Video</b><br><b>Sync</b><br><b>Frequency</b>   | RGB analog, NTSC, PAL-M, PAL-N, SECAM, HDTV<br>Separated and composite<br>Fh: 15~80kHz; Fv: 56~120Hz  |
| COMPATIBILITY          | <b>PC</b><br><b>Mac</b> ®††   | From SVGA up to SXGA<br>Up to SXGA (may require Mac Adapter)  |
| CONNECTOR              | <b>RGB Input</b><br><b>RGB Output</b><br><b>Composite Video</b><br><b>Component Video</b><br><b>S-Video</b><br><b>Audio (In/Out)</b><br><b>Controls</b><br><b>USB</b> | 15-pin HD, D-sub (x2)<br>15-pin HD, D-sub (x1)<br>RCA (x1)<br>RCA (x3)<br>Mini-Din 4 pin (x1)<br>In RCA (x1) and 3.5mm (x2); Out 3.5mm (x1)<br>15-pin D-sub (x1)<br>USB upstream (x1) available through RS232 port  |
| POWER                  | <b>Voltage</b><br><b>Frequency</b><br><b>Consumption</b>  | 90-132V AC/198-264V AC<br>50-60Hz (universal)<br>290W (typ)   |
| USER CONTROLS          | <b>Basic</b><br><br><b>Remote</b><br><br><b>OnView</b> ®  | Standby on/off, menu (left, right, up, down), input, reset, mute, keystone, indicator (lamp, power, temp)<br>Standby on/off, video, laser, blank, RGB, disk pad, auto, mouse, menu, position, menu select (left, right, up, down), reset, freeze, magnify (+, -, off), volume (up, down), mute, timer<br>Brightness, contrast, V. position, H. position, H. phase, H. size, color balance (red), color balance (blue), aspect ratio, auto, RGB, keystone, blank, mirror, start up, volume, menu color, timer, language, auto off, sync on green |
| OPERATING CONDITIONS   | <b>Temperature</b><br><b>Humidity</b>   | 32° F–95° F (0° C–35° C)<br>10%–85% (non-condensing)  |
| DIMENSIONS (W x H x D) | <b>Physical</b>   | 298mm x 76mm x 228mm<br>(11.7" x 3.0" x 9.0")   |
| WEIGHT                 | <b>Net</b><br><b>Gross</b>  | 3.25 kgs. (7.2 lbs.)<br>7.5 kgs. (16.5 lbs.)  |
| REGULATIONS            |   | UL, FCC-B, c-UL, CE, CB Report, TUV/GS, CB Report, VCCI, BSMI, PCT  |
| OTHER                  |   | Mirror reverse image, upside down image, digital keystone correction, DDC 1/2B  |
| WARRANTY               |   | Three-year limited warranty on parts and labor, first year Express Exchange® service, one-year warranty on lamp.  |



**ViewSonic®**  
See the difference.®